



# Çok Amaçlı Test Aletleri

beek

BEEK bir Bimel Markasıdır.

## UTP Kablo Test Aleti



### BT-MS6816

Multi-Functions wire tracker

#### Features

**Wire track** Directly track wire type: RJ45,RJ11  
Track other wire through the attachment

#### Sequence collation

Open circuit, short circuit,  
detection of cable line sequence

#### Network wire collation

Test device used with UTP (Unshield Twisted Pair)  
and STP (Shield twisted Pair) wiring

#### DC level test

Tests for open circuits, shorts, miswires,  
reversals, and split pairs

#### Telephone line test

Allow one person to test T568A, T568B,  
10Base-T, and Token Ring

#### Continuity

DC level test

#### Switch port collation

Identify the state of working telephone  
line(clear,ringing,busy)  
Judge continuity of the cables or wires  
Detection switch connected condition

## Kablo Test Cihazı ve Tone Tracer



### BT-ST308-8

Kablo test cihazı ve Tone Tracer, 8 uç birimi

#### Features

- One person enough to complete cable continuity check.
- Directly hunt 5E, 6E, telephone wire, coaxial cable, USB cable and other cables.
- Check wiring error in 5E, 6E, telephone line, coaxial cable, USB cable and such as open circuit, short circuit, jumper wire, reverse connection or cross-talk interference.
- Locate the wiring or connection error.
- Measure cable length and determine the distance of open circuit and short circuit.
- Dynamically calibrate cable length and make length measurement as accurate as 97%.
- Simple and easy use. Big screen to display test result clear.
- Portable unit with long battery life (wait-case 50 hours).
- Automatically time-delay shut off and backlight display function.
- Measure length and pair with or without far-end recognizer.
- Locate cable and there are 8 far-end passive test jacks
- Far-end recognizer with prompting voice.
- Self-checking function and automatically compensate any change in battery capacity or ambient temperature.
- Single board computer software watchdog design and reliable operation.

## Lazer Mesafe Ölçer



### BT-ST80

Lazer Mesafe Ölçer

#### Features

- Quick measurement of distance , lengths, widths, heights , areas and volumes
- Wide measuring range up to 80m with  $\pm 2$ mm accuracy
- Spirit bubble guarantee better accuracy
- Pythagoras measurement
- For both indoor and outdoor measurement
- Addition and Subtraction function
- Front and rear edge switchable
- 99 data records and recall
- Large clear LCD with backlight
- Outdoor target reflection board
- Max and Min value display
- Multi-line display several readings simultaneously
- selectable meter (m), inch (in) and feet (ft)
- Auto power off

#### Specification:

**Range** :0.2- 80m ; 0.65in-262.5ft

**Accuracy** :  $\pm 2$ mm ;  $\pm 0.07$ in

**Memory**: 99 data

**Laser type** : 635nm, <1mW ,class II

**Operation temperature** : 0-40°C (32-104°F)

**Storage temperature** : -10-60°C(14-140°F)

**Auto laser off**: 20S

**Auto power off**: 150S

**Power supply**: 3\*1.5V. AAA

**Size**: 118\*54\*28mm

**Weight**: 140g (batteries included)

## Dijital Multimetre



### BT-MS86

Dijital Multimetre

#### Features

- AC/DC Volt, AC/DC Amp, Ohm, Kapasitans, Frekans, Sıcaklık ölçümleri. 4000 count göstergesi. Max/Min değeri tutma, Data tutma, Temassız Voltaj Algılayıcı, Diyot ve Transistör testleri, Temas sürekliliği, Ekran aydınlatması.

## Dijital Multimetre



### BT-MS8233D

Dijital Multimetre

#### Features

- AC/DC Volt, AC/DC Amp, Ohm, Frekans ölçümleri. 2000 count göstergesi. Max değeri tutma, Data tutma, Diyot testi, Temas sürekliliği, Ekran aydınlatması.

## Toprak Hattı Test Cihazı



### BT-ST2306

Toprak Hattı Test Cihazı

#### Features

- 2/3/4-wires accurate measurement of earth resistance, Soil resistivity and earth voltage, etc.
- Anti-interference design, high precision, stability and reliability
- Data logging 999 group and USB interface to computer
- Data hold for easy reading
- Earth resistance alarm
- Overflow & low battery indication
- 4-digits large and clear LCD display with analog bar graph and blue backlight
- Safety as per IEC 1010-1 cat.III 600V

#### Specifications

**Voltage**: AC48V rms

**Measuring current**: 20mA AC max

**Frequency**: 128Hz / 111Hz / 105Hz/94Hz/AFC  $\pm 1$ Hz

**Range**: 2 pole & 3 pole: 0.01~19.99K $\Omega$ ;  $\pm(2.0\%rdg + 3dgt)$

4 pole ,Soil resistivity : 0.06~19.99K $\Omega$ ;  $\pm(2.0\%rdg + 3dgt)$

**Display**: LCD Display(102 x86.6 mm),Backlit

**USB2.0 Interface data storage**: 999 groups

**Batteries**: 1.5V X 6,R14S

**Dimensions**: 270 x 190 x 80 mm

**Weight**: approx.4.0kgs

**Accuracy**: tool case,wires&earthing rods.

Merkez-Ankara : Bayındır Sok. 5/4-7 Yenışehir 06410 ANKARA Tel: +90 (312) 434 22 45

Bimel İstanbul : Büyükdere Cad. 78/80 Akabe İş Merkezi No: 5 Mecidiyeköy 34390 İSTANBUL Tel:+90 (212) 347 75 40

Network Şube-İstanbul : Kozyatağı Sok. Parlarbaşıoğlu Apt. 28/42 Kozyatağı 34742 İSTANBUL Tel: +90 (216) 384 50 61

Şube-Bursa : Sakarya Mah. Sezen Sok. ALİHAN No: 7/2 16220 OSMANGAZI-BURSA TEL: +90 (224) 274 00 55

Bimel İzmir Ltd.: Fevzi Paşa Bulvarı 1363 Sok. 1/305 35230 Çankaya/İZMİR Tel: +90 (232) 489 07 55

E Posta : bimel@bimel.com.tr / Web : www.bimel.com.tr

bimel