

## Fiber Pigtail

Connector type	FC/SC/LC/ST			
Diameter (mm)	0.9mm with LSZH sheath			
Mode	SM		MM	
Type	PC	UPC	APC	PC
Insertion Loss(dB)	≤0.30	≤0.30	≤0.20	≤0.30
Return Loss	≥45dB	≥55dB	≥65dB	≥45dB
Exchangeability(dB)	≤0.20			
Repeatability(dB)	≤0.10			
Operation Temperature	-40°C-- +80°C			
Storage Temperature	-40°C-- +85°C			
Durability	> 1000 times			
Industry Standard	IEC-61300-3-4 & IEC-61300-3-34			

**BC-FO-PT5ST-01**

ST/UPC Fiber PigTail,  
50/125 μ, multimode,  
0.9mm simplex,  
1 metre, Class OM2

**BC-FO-PT5LC-01**

LC/UPC Fiber PigTail,  
50/125 μ, multimode,  
0.9mm simplex,  
1 metre, Class OM2

**BC-FO-PT9ST-01**

ST/UPC Fiber Pigtail  
0.9mm SX  
1 metre  
OS1/OS2,OS1/OS2

**BC-FO-PT9SC-01**

SC/UPC Fiber PigTail,  
9/125 μ, singlemode,  
0.9mm simplex,  
1 metre, Class OS2,

**BC-FO-PT5SC-01**

SC/PC Fiber PigTail,  
50/125, multimode,  
0.9mm simplex,  
1 metre, Class OM2

**BC-FO-PT5LC-01/3**

LC/UPC Fiber PigTail,  
50/125 μ, multimode,  
0.9mm simplex,  
1 metre, Class OM3

**BC-FO-PT5SC-01/3**

SC/UPC Fiber PigTail,  
50/125 μ, singlemode,  
0.9mm simplex,  
1 metre, Class OM3

**BC-FO-PT5SC-01/4**

SC/UPC Fiber PigTail,  
50/125 μ, multimode,  
0.9mm, simplex,  
1 metre, Class OM4,

**BC-FO-PT9LC-01**

LC/UPC Fiber PigTail,  
9/125 μ, Singlemode,  
0.9mm simplex,1 metre  
Class OS2