

BS-HE12

100m HDMI Exender PoC (Power over Cable)

beek

Extends the transmission range of 1080P HDMI video up to 100m by using single CAT6/7 UTP cable.

Features:

Extends 1080P 60Hz video up to 100m
HDMI 1.3 HDCP 1.4
Max resolution 1920x1080 60Hz
Max distance 100m over CAT6/7 UTP cable
PoC (Power over Cable)
Only one power adapter required

Specifications



Connectors	
Sender (KVM)	Input: HDMI Type A (F) x1, Output: RJ45 x1
Receiver (Console)	Input: RJ45 x1, Output: HDMI Type A (F) x1
Video Formate	1080P 60Hz, HDMI 1.3, HDCP 1.4
Resolution	Max 1920x1080 60Hz
Max Distance	100m by AWG24 CAT6 UTP
LED Indicators	HDMI LED x1
Power	Input: DC jack (black) Adapter: Input AC 100-230V, output DC 5V 2A, 1PC for Sender or Receiver: (PoC)
Physical Prop.	Metal
Housing	0.29KG (sender + receiver)
Weight	Sender: 9.7x9x3cm; Receiver: 9.7x9x3cm
Dimension	Sender: 9.7x9x3cm Receiver: 9.7x9x3cm
Environment	Operating Temp.: 0-40° C Humidity: 5-85%RH (non-condensing)