



BN-PP-648U

48 Port Cat6 UTP Patch Panel, 8P8C, Gold contact,LSA, 2U, unshielded, with cable holder

Category 6 Patch Panel are based on 19" frame dimensions and have 48 modular jack RJ45 ports on 2U. The Category 6 Patch Panel will support the following applications, such as:

- 1000BASE-T (Gigabit Ethernet), 10GBASE-T
- 622 Mbps ATM, 1.2 Gb/s ATM.
- Token ring 4/16.
- Digital video and broadband/baseband analog video.
- Voice over Internet Protocol (VoIP).
- Power-Over-Ethernet (PoE, PoE+).
- TP-PMD.
- ISDN.

Transmission Standard	ANSI/TIA-568-C.2 ISO/IEC 11801
Total Ports, quantity	48
SIZE	L 481.5mm x W 89.2mm x H 34.65mm
Color	Black
Label	Write-on label, easy to identify
Package Quantity	1
Packaging Type	Bag
Rack Type	EIA 19 in Rack Units 1.0

General Specification Mechanical Specification

Panel Style	Straight
Material Type	High-impact, flame retardant, thermoplastic Steel
Panel Mounting	Flush
Metal Cable Management	Optional
Termination Type	IDC Wiring T568A T568B
Conductor termination range	22 AWG - 26 AWG
Conductor type	Solid or Stranded
Jack Termination Durability	>750 times
IDC Termination Durability	>250 times
Dust Cover	Yes

Electrical Specification

Contact Resistance	20 M Ω
Current Rating	1,5 Amps
DC Resistance	Max. 0,1 Ω