

BN-GS-1242S

24 Ports Gigabit Ethernet switch with 2G SFP

beek



Chassis
Installation

Plug & Play

6KV
Lightning Protection

Key Features:

Ports: Provide 24*10/100/1000Mbps Ethernet ports with 2 1000M SFP Uplink

Self-adaption: RJ45 port supports 10/100/1000Mbps Auto MDI/MDIX

Fiber Port: 2 1000Mbps SFP Uplink

Wide Application: Designed for Wifi AP and IP Security camera.VoIP etc

Surge protection: Protect the device from lighting surges and others electrical hazards

Considerate Design: Wall mounted with fanless design

Easy to use: Plug and play, No configuration required

Installation: Rack mount with easy installation

High performance switch with 2 gigabit SFP Uplink

This 24 ports gigabit Switch provides a high-performance switch architecture that is capable of providing the non-blocking switch fabric and wire-speed throughput as high as 64Gbps, which greatly simplifies the tasks of upgrading the LAN for catering to increasing bandwidth demands. Besides, the Flow Control function of the switch enables routers and servers to directly connect to the Switch for fast and reliable data transfer.

All the RJ45 copper interfaces of the BN-GS-1242S support 10/100/1000Mbps auto-negotiation for optimal speed detection through RJ45 Category 6, 5 or 5e cables. It also supports standard for auto-MDI/MDI-X that can detect the type of connection to any Ethernet device without requiring special straight or crossover cables. With 2 SFP module slot available, the SFP uplink port is ideal for connecting the switch to the network's backbone, providing more than enough bandwidth and stability for ultra high speed data transferring, Beside the SFP can transmit the data with Max 100Km distance with more economic solution

Excellent Traffic Transmission

The BN-GS-1242S supports Store-and-Forward forwarding scheme to ensure low latency and high data integrity, which eliminates unnecessary traffic and relieves congestion on critical network paths. With an intelligent address recognition algorithm. The high data throughput and 64Gbps internal switching fabric make it ideal for most Gigabit environments, especially when network is upgraded to a Gigabit environment.

Fanless Design

With its good ventilation design, this switch is able to operate all along without a fan, thus reducing substantial power consumption and creating a noiseless environment. It is definitely the best choice for any working environment without affecting its performance.

BN-GS-1242S

24 Ports Gigabit Ethernet switch with 2G SFP



Technical Datasheet


Model	BN-GS-1242S	
Hardware Specifications		
Connector	24 10/100/1000BASE-T RJ45 auto MDI/MDIX ports 2 1000 Base-X SFP Slots Ulink	
Uplink port	2 1000 Base-X SFP Slots	
LED Display	Power Indicator: PWR(green). Network Indicator: Link(yellow) SFP: Green	
Thermal Fan	Fanless Design	
Network Standard	IEEE802.3i 10 BASE-T IEEE802.3u 100 BASE-TX IEEE802.3ab/z 1000 BASE-TX IEEE802.3x Flow Control IEEE802.3az EEE	
Switch Architecture	Store and Forward	
Transmission model	IEEE802.3X full-duplex and Backpressure half-duplex	
Switch Performance	Backplane bandwidth	64Gbps
	Packet forwarding rate	47.62Mpps
	MAC address	16k
Power requirement	AC100-240V 50/60Hz	
ESD Protection	6KV ESD	
Dimension	440 x 180 x 45mm (W x D x H)	
Weight	2.2 kg	
Environment	Operating temperature: -10℃ ~ 45℃ operating humidity: 10%~90% Storage temperature: -20℃ ~ 70℃ storage humidity: 5%~95%	
Safety	FCC Part15 Class A,CE,RoHs	
MTBF	49,325 hours	

BN-GS-1242S


24 Ports Gigabit Ethernet switch with 2G SFP

beek

Interfaces



Structure Diagrams




BN-GS-1242S

24 Ports Gigabit Ethernet switch with 2G SFP

beek

Applications



Ordering Information

BN-GS-1242S

24 Ports 10/100/1000Mbps Ethernet switch with 2 Gigabit SFP Uplink, 6KV surge protection